

13790510059

5

4

3

2

1

3.00

 $1.60 \pm 0.25$  $1.7 \pm 0.20$ 

A-A SECTION

 $0.18 \pm 0.08$  $1.75 \pm 0.15$  $0.9 \pm 0.08$ 

C-C SECTION

 $1.2 \pm 0.15$  $1.15 \pm 0.15$ 

B-B SECTION

 $1.2 \pm 0.25$  $1.55 \pm 0.15$ 

EST1252 T P X - 2 X - X

舜通代码+间距

T示意端子

X普通  
L长  
S短

0素材  
2镀锡先冲后镀  
3镀锡先镀后冲  
4镀全银(镀后冲)  
4.2镀全银先冲后镀  
5G、15G示意镀金5U"或15U",  
16示意镀金1U"

P磷铜  
B黄铜  
E合金铜

## NOTES:

1. Material:C5191
2. Color:
3. Corrent Roting:1A AC,DC
4. Voltage rating:150V AC,DC
5. Temperature Rang:-25° c~+85° c
6. Contoct Resistance:30mΩ Min
7. Insulation Resistance:500MΩ Min
8. Withstanding Voltage:500V AC/minute
9. APPLICABLE WIRE:AWG#28~#32
10. Q' TY:15000PCS/REEL



DGEASTOM

东莞市舜通实业有限公司

DONGGUAN EASTOM ELECTRONIC Co.,Ltd.

料号PART NO: EST1252TPX-2X-G

品名 TITLE: DF13-T

材料:

单位: MM

包装规格:

比例: 1:1

制图:

审核:

核准:

日期:

2023.05.22

一般公差  
GENERAL TOLERANCE  
X.X ±0.30  
X.XX ±0.20  
ANGLE ±1°



EST