


SECTION a-a

SECTION b-b



SECTION c-c

EST2008 T P X - 2 X- X  
 界通代码+间距  
 T 示意端子  
 X 普通脚  
 H 高脚  
 E 增高型脚  
 L 长脚  
 S 短脚  
 X 端  
 G 母端  
 C 示意 90°  
 S 示意 180°  
 0 素材  
 2 锡锡先冲后镀  
 3 锡锡先冲后镀  
 5G, 15G 示意镀金 5U° 或 15U°, 1G 示意镀金 1U°  
 P 铜  
 B 黄铜  
 E 合金铜

**技术参数 SPECIFICATIONS**  
 ■ 适用线规: AWG#26~#32  
 Applicable wire: AWG#26~#32  
 ■ 额定电压: 250V DC/AC (有效值)  
 Voltage rating: 250V DC/AC (rms)  
 ■ 额定电流: 2.5~1.0A  
 Current rating: 2.5~1.0A  
 ■ 耐压值: 800V AC(有效值)  
 Withstand voltage: 800V AC(rms)  
 ■ 工作温度: -25°C~+85°C  
 Working Temperature: -25°C~+85°C  
 ■ 绝缘电阻: ≥1000MΩ  
 Insulation resistance: ≥1000MΩ  
 ■ 接触电阻: ≤0.02Ω  
 Contact resistance: ≤0.02Ω

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 淮 APPROVALBY	制图: 审核: 核准: 日期: 2022/12/03	一般公差 GENERAL TOLERANCE X.X ±0.30 X.XX ±0.20 ANGLE ±1°



东莞市羿通实业有限公司  
 DONGGUAN EASTOM ELECTRONIC Co., Ltd.