

13790510059

5

4

3

2

1

Circuit NO.

Pin No.	A	B	C
2P	2.00	5.10	5.80
3P	4.00	7.10	7.80
4P	6.00	9.10	9.80
5P	8.00	11.10	11.80
6P	10.00	13.10	13.80
7P	12.00	15.10	15.80
8P	14.00	17.10	17.80
9P	16.00	19.10	19.80
10P	18.00	21.10	21.80
11P	20.00	23.10	23.80
12P	22.00	25.10	25.80
13P	24.00	27.10	27.80
14P	26.00	29.10	29.80
15P	28.00	31.10	31.80

 $C \pm 0.35$

5.7

 $B \pm 0.30$

2Pin

 3.5 ± 0.25 3.1 ± 0.25 3.5 ± 0.3

3Pin

 2.55 ± 0.2

4Pin以上

 2 ± 0.15 0.62 0.62

4Pin_3D示意图

EST2036 H - 1*NP X - X - X - HF-NK - X

↑
羿通代码+间距

↑
PIN数
1示意单排
2示意双排

↑
X*线
B*线
R*线
L*线
Y*线
C*线
C*线

↑
X*线
B*线
C*线
2L*线
U*线
HV*线
LC*线
K*线
E*线

↑
NO MARK

↑
HF示意无卤
NF普通含卤

↑
A*线750
B*线850
X*普通料

H示意胶壳,
H后无数字默认材质V0
H后带数字2示意材质V2

SPECIFICATIONS

- Voltage rating:100V AC/DC;
- Current rating:2A AC/DC;
- Withstanding Voltage:800V AC/minute
- Insulation resistance:1000MΩ Min
- Temperature range:-25℃~+85℃
- Contact resistance:30mΩ Max



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.


料号PART NO: EST2036H-1*NPX-X-X

品名 TITLE: 51065-H

材料: 单位: MM 包装规格: 比例: 1:1

制图: 审核: 核准: 日期: 2023. 12. 10

一般公差
GENERAL TOLERANCE
X. X ±0.30
X. XX ±0.25
ANGLE ±1°



LS