

Technical drawing of a component featuring a top row of seven vertical slots and a bottom row of seven mounting holes. The top row has a total width of 2.5 ± 0.1 and a center slot width of $A \pm 0.25$. The bottom row has a total width of $B \pm 0.35$. Each slot has a diameter of $\phi 0.70$.

P.C.B LAYOUT

A technical drawing of a U-shaped metal bracket. The height of the bracket is labeled as 6.0. The top horizontal distance between the two vertical legs is labeled as 4.8. The side width, or the distance between the two U-shaped notches, is labeled as 3.5. The drawing shows the bracket's profile with its two vertical legs and the central U-shaped cutout.

Poles	DIM.A	DIM.B
2P	2.5	7.4
3P	5.0	9.9
4P	7.5	12.4
5P	10.0	14.9
6P	12.5	17.4
7P	15.0	19.9
8P	17.5	22.4
9P	20.0	24.9
10P	22.5	27.4
11P	25.0	29.9
12P	27.5	32.4
13P	30.0	34.9
14P	32.5	37.4
15P	35.0	39.9

- SPECIFICATIONS
- Voltage rating: 250V AC/DC;
- Current rating: 2.5A AC/DC;
- Withstanding Voltage: 800V AC/minute
- Insulation resistance: 1000MΩ Min
- Temperature range: -25°C ~ +85°C
- Contact resistance: 20mΩ Max
- Applicable wire: AWG#28 ~ AWG#22



东莞市羿通实业有限公司 DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO:EST2505WR-1*NPX-X

一般公差
GENERAL TOLERANCE
X,X $\pm 0.$
X,XX $\pm 0.$
X,XXX $\pm 0.$
ANGLE $\pm 1^{\circ}$

品名 TITLE:5264-WAFER弯针

X.XXX ±0.
ANGLE ±1°

材料	单位:	MM	包装规格:	比例:	1:1	X,XXX ANGLE ±1°
Y	制图:	审核:	核准:	日期:	2022/7/2	 