

13790510059

5

4

3

2

1.00

 $3.8 \pm 0.20$  $7 \pm 0.25$  $2.54 \pm 0.20$ 

2.5

2.54

 $A \pm 0.25$ 

1.00

1.00

 $B \pm 0.35$ 

0.7

 $15.3 \pm 0.35$ 

2P

3P

04P-20P

3P

| PART NO | Dimension |       | PART NO | Dimension |       |
|---------|-----------|-------|---------|-----------|-------|
|         | A         | B     |         | A         | B     |
| 02      | 2.54      | 5.08  | 11      | 25.40     | 27.94 |
| 03      | 5.08      | 7.62  | 12      | 27.94     | 30.48 |
| 04      | 7.62      | 10.16 | 13      | 30.48     | 33.02 |
| 05      | 10.16     | 12.70 | 14      | 33.02     | 35.56 |
| 06      | 12.70     | 15.24 | 15      | 35.56     | 38.10 |
| 07      | 15.24     | 17.78 | 16      | 38.10     | 40.64 |
| 08      | 17.78     | 20.32 | 17      | 40.64     | 43.10 |
| 09      | 20.32     | 22.86 | 18      | 43.10     | 45.64 |
| 10      | 22.86     | 25.40 | 20      | 48.18     | 50.72 |

## SPECIFICATIONS:

1-Voltage rating:250V AC/DC;

2-Current Rating:2.5A AC/DC;

3-Withstanding Voltage:1000V AC/minute;

4-Temperature Range:-25°C~+85°C;

5-Insulation Resistance:1000mΩ

6-Cpmtact Resostamce:20mΩ

7-Material:PA66



东莞市羿通实业有限公司  
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2517H-1\*NPX-B-X

品名 TITLE: YCDG-H

材料: PA66UL94-V0

单位: MM

包装规格: 1K/包

比例: 1:1

制图: LI

审核: LI

核准: LI

日期: 2022/04/12

| 一般公差<br>GENERAL TOLERANCE |               |
|---------------------------|---------------|
| X.X                       | $\pm 0.30$    |
| X.XX                      | $\pm 0.20$    |
| ANGLE                     | $\pm 1^\circ$ |

| 版次<br>REVISION | 日期<br>DATE | 变更内容<br>DESCRIPTION | 核 准<br>APPROVALBY |
|----------------|------------|---------------------|-------------------|
|                |            |                     |                   |
|                |            |                     |                   |
|                |            |                     |                   |

ZL