

13790510059

5

4

3

2

3.96±0.08

1.00±0.15

13.40±0.20

7.16±0.15

7.30±0.15

B±0.30

PART NO	Dimensions		
	A	B	C
1*2	3.96	8.02	3.65
1*3	7.92	11.98	
1*4	11.88	15.94	
1*5	15.84	19.90	
1*6	19.80	23.86	
1*7	23.76	27.82	
1*8	27.72	31.78	
1*9	31.68	35.74	
1*10	35.64	39.70	
1*11	39.60	43.66	
1*12	43.56	47.62	
1*13	47.52	51.58	
1*14	51.48	55.54	
1*15	55.44	59.50	

EST3960 H - 1*NP X - B - X - HF-NK - X

↑ 异通代码* 间距

↑ PIN数
1示意单排
2示意双排

↑ X*壳
B*菲
C*胶
L*壳
Y*壳
G*壳
E*壳

↑ X*胶壳
G*胶壳

↑ NO MARK

↑ A*热丝750
B*热丝850
X*普通料

↑ HP示意无卤
NP普通含卤

H示意胶壳,
H后无数字默认材质V0
H后带数字2示意材质V2

SPECIFICATIONS

Applicable wire:AWG#18~#22

Voltage rating: 250V DC/AC (rms)

Current rating:10A

Withstand voltage: 800V AC(rms)

Working Temperature:-25℃+85℃

Insulation resistance:≥1000MΩ

Contact resistance:≤0.02Ω

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY




东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST3960H-1*NPX-B-X

品名 TITLE: VH3.96-H公

材料: PA66	单位: MM	包装规格: 1K/包	比例: 1:1
制图:	审核:	核准:	日期: 2022/11/09

一般公差
GENERAL TOLERANCE
X.X ±0.30
X.XX ±0.20
ANGLE ±1°



EST