

13790510059

5

4

3

2

1

 $B \pm 0.40$ $\square 0.15 \text{ MAX}$ 3.15 ± 0.30 11.8 ± 0.30 9.25 ± 0.3

17.3

Assembly Layout

2P

3P

 $A \pm 0.3$ 1.14 ± 0.08 3.96 ± 0.15

6.2

 $C \pm 0.35$

A

3.96

1.8

1.67

1.5

7.5

10.75

2.5

Mating PCB detail

Circuits	Dimensions (mm)		
	DIM. A	DIM. B	DIM. C
02	3.96	11.88	8.60
03	7.92	15.84	12.56
04	11.88	19.80	16.52
05	15.84	23.76	20.48
06	19.80	27.72	24.44
07	23.76	31.68	28.40
08	27.72	35.64	32.36
09	31.68	39.60	36.32
10	35.64	43.56	40.28
11	39.60	47.52	44.24
12	43.56	51.48	48.20
13	47.52	55.44	52.16
14	51.48	59.40	56.12
15	55.44	63.36	60.08
16	59.40	67.32	64.04

SPECIFICATIONS

- Poles: 02 To 16
- Voltage rating: 250V AC/DC;
- Current rating: 7A AC/DC;
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000M Ω Min
- Temperature range: -25°C ~ +85°C
- Contact resistance: 20m Ω Max



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号 PART NO: EST3960WVS-1*NPX-X

品名 TITLE: VH3.96立贴

材料:

单位:

MM

包装规格:

比例:

1:1

制图:

审核:

核准:

日期:

2025/9/5

一般公差
GENERAL TOLERANCE
X.X ± 0.25
X.XX ± 0.20
ANGLE $\pm 1^\circ$

日期版次
REVISION日期
DATE变更内容
DESCRIPTION核 准
APPROVAL BY

6

5

4

3

2

1

ZT