

**SPECIFICATIONS**

- Voltage rating: 250V AC/DC;
- Current rating: 8A AC/DC;
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000MΩ Min
- Temperature range: -25°C ~ +85°C
- Contact resistance: 20mΩ Max
- Material: PA66

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核准 APPROVALBY

EST3961 H - 1*N_P X - B - X - HF-NK - X
 界通代码+间距
 PIN数
 1示意单排
 2示意双排
 H示意胶壳,
 H后无数字默认材质V0
 H后带数字2示意材质V2
 X普通
 B黑色
 C耐破
 L示锁
 U超塑P防呆型
 HV带高凸点
 LC带低凸点
 Y黄色
 G绿色
 K卡槽
 E有耳
 X公胶壳
 G母胶壳
 NO MARK
 A灼热丝750
 B灼热丝850
 X普通料
 HP示意无卤
 NF普通含卤

P NO.	Dimensions		
	A	B	C
1*2P	3.96	8.4	7.57
1*3P	7.92	12.4	11.53
1*4P	11.88	16.3	15.49
1*5P	15.84	20.3	19.45
1*6P	19.80	24.3	23.41



东莞市羿通实业有限公司
 DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号 PART NO: EST3961H-1*N_PX-B-X

一般公差
 GENERAL TOLERANCE
 X. ±0.25
 X.X. ±0.15
 X.XX. ±0.05
 ANGLE ±1°

品名 TITLE: MX3.96-H

材料: PA66-v2	单位: MM	包装规格: 1K/包	比例: 1:1
制图: LI	审核: LI	核准: LI	日期: 2022/08/12