



EST4501 T P X - 2 X- X  
 T: 示意端子  
 P: 磷铜  
 X: 普通脚  
 X: 普通  
 X: 高脚  
 X: 长  
 H: 增高型脚  
 E: 增高型脚  
 L: 短  
 E: 合金铜  
 U: 超薄  
 0: 素材  
 2: 镀锡先冲后镀  
 3: 镀锡先镀后冲  
 4: 镀全镀(镀后冲)  
 4.2: 镀全镍先冲后镀  
 5G: 15G示意镀金5U<sup>°</sup>或15U<sup>°</sup>, 1G示意镀金1U<sup>°</sup>

范围	>0~3	>3~18	>18~50	>50~120
公差	±0.12	±0.15	±0.3	±0.5

Poles :2to 4;  
 Cerrebt rating:10AC DC;  
 Votateg rating:300V AC DC;  
 Termperature range:-25°C To+85°C  
 Contact resistance: $\leq 20\text{M}\Omega$   
 Insulation resistance: $\geq 1000\text{M}\Omega$   
 Withstand voltage:1500V AC/Minute  
 Applicable wire:AWG#26 to AWG#18

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 淮 APPROVALBY	制图: 审核: 核准: 日期: 2022. 9. 6	一般公差 GENERAL TOLERANCE X.X ±0.30 X.XX ±0.20 ANGLE ±1°



东莞市羿通实业有限公司  
 DONGGUAN EASTOM ELECTRONIC Co., Ltd.